

# Rectangular Duct Line ■

## Rectangular duct production line

Automatic rectangular duct production line for shearing, notching, beading and folding. Entry-level configuration for duct factories producing rectangular duct in medium volumes. Integrates with TDC/TDF flange forming.



### Technical specifications

Parameter	Specification
Model	SBAL-II-1250 / SBAL-II-1550
Thickness	0.5–2.0 mm
Max width	1250 / 1550 mm
Max feeding speed	18 m/min
Max weight capacity	8000 kg
Power	9.2 kW
Weight	3000 / 3500 kg
Mainframe dimension	1900×1800×1400 / 1900×2100×1400 mm
Decoiler dimension	2300×1750×1650 / 2300×2050×1650 mm
Voltage	380V / 50Hz / 3PH

**Australian supplier** of HVAC duct machinery · manufacturing since 1995 · ISO 9001:2015 · CE certified · 5,000+ machines installed in 100+ countries

**Request a quotation** — a mechanical engineer (not a salesperson) replies within 12 hours. [sales@sbkjduct.com](mailto:sales@sbkjduct.com)  
· [sbkjduct.com/product/rectangular-duct-line-ii.html](https://sbkjduct.com/product/rectangular-duct-line-ii.html)

Specifications taken from the SBKJ Product Catalog 2026 and are subject to change without notice. © SBKJ Group · sbkjduct.com